



DeTAG 266

from the Makers of
InnerCrete™ Membrane Technology

GRAFFITI, TAG & PAINT REMOVER OFF PAINTED SURFACES

“Protecting Concrete from the Inside...Out”

DeTAG – from the Makers of InnerCrete™ Membrane Technology, is an advanced, eco-friendly cleaner designed to remove graffiti, tags and paint off painted and other non-porous surfaces without damage to the underlying painted surface.

DeTAG is specially formulated to remove graffiti and tags off surfaces such as:

- Most painted surfaces
- Lexan (and other polycarbonates)
- Plexiglas (and acrylics)
- Clear coat on vehicles
- Glass
- Metals and alloys

DeTAG will not destroy or discolor the underlying surface. It has a very low, harmless odor and can be used indoors and outdoors without harm to the user. As with any graffiti remover product, ALWAYS TEST A SMALL AREA FIRST. This product should not be used on signs with reflective coatings.

Fully biodegradable and ready to use, **DeTAG** is effective in the removal of:

- Paint and overspray
- Grease
- Crayon and wax
- Tape and adhesive residues
- Felt markers
- Graffiti inks and paints
- Lipstick
- Scuff marks

DeTAG is very cost effective; it requires very little chemical to achieve results, it reduces man-hours and effort to complete projects and reduces the amount of waste produced in the removal effort.

Applications:

- Graffiti & tag removal off painted surfaces
- Lexan or Plexiglass bus shelters
- Adhesive residues left from tape or glue
- Unwanted overspray on vehicles, etc from painting projects
- Brake dust from car wheels
- Stadiums, arenas and public facilities
- Scuff marks off polished floors



DeTag Remover 266

v20100625

Protocol Products offer a complete graffiti removal and protection system:

GraffitiGone Remover - for the removal of graffiti paint (from aerosol cans) off unpainted concrete, cement-based and porous surfaces, **DeTAG** - for graffiti, tag and paint removal off painted and non-porous surfaces, and **GraffitiGuard Anti-Graffiti Barrier** - a permanent treatment for concrete for protection against future graffiti.

Benefits:

- Fully biodegradable
- Non-toxic, non-carcinogenic
- Eco-friendly
- Low, inoffensive odor
- Will not fog Plexiglass, Lexan or glass
- Will not damage most underlying paints
- Ready to use, easy application
- Cost effective

Surface Preparation:

DeTAG should be applied in weather above 5°C. Warmer ambient and surface temperatures will increase activation and reduce dwell time. **Always test a small area to determine color fastness and removal time.** Ensure all areas not to be cleaned are suitably protected. There is no need to prewash the surface before application. If treating horizontal surfaces, there should be no pooling of water on the surface as this will dilute the product. This product should NOT be diluted and does not need any mixing before application.

Dwell Time:

Dwell time will depend on several factors, type of material to be removed, type and temperature of substrate and number of layers of graffiti to be removed. Do not let **DeTAG** stay on surface for longer than 15 minutes. If removal is not complete, wipe off product and reapply.

Application:

Apply a generous amount of **DeTAG** by spray, brush, roller or rag to fully saturate the problem substance to be removed. Larger areas are best tackled with spray application, such as a hand sprayer or garden sprayer that produce a fine atomized mist, so as to ensure even coverage and minimal product waste. Smaller areas can be tackled with any of the above application methods.

Removal:

Product can be removed from small areas using dry cloth, then rinsed with warm or soapy water to remove residue. For larger surfaces product can be removed using a pressure washer at a low psi.

CAUTION:

Weak paints like interior latex will also be softened and slightly removed by **DeTAG**. To clean these types of surfaces, several applications with dwell times of no more than one minute will be required. Wipe product off surface with a damp cloth after each application. The surface paint will re-harden to its original color and finish in a few hours. **Always test a small area of these types of surfaces.**

Packaging

US 5 gallon (18.9L) pail
1 litre spray bottle (US .265G)

Coverage:

Approximately 150-250 sq feet / US gallon.

Safety:

Proper safety precautions should be followed at all times. Avoid contact with eyes and skin. Flush with water if contact does occur. Keep out of reach of children. Use in areas with adequate ventilation.

Protocol Concrete Protection Products
and proprietary
InnerCrete™ Membrane Technology
developed and owned by:

PROTOCOL
Environmental Solutions Inc.

#105B 81 Golden Drive
Coquitlam, British Columbia V3K 6R2
Canada
Tel: 604-464-0660
Toll free: 1-877-464-0662

www.innercrete.com