



## **Xtreme Marine WashDown Product Data Sheet & Application Instructions**

### **STAIN & RUST REMOVER FOR GEL COAT & MOST MARINE SURFACES**

**Xtreme Marine WashDown is an effective boat and gel coat cleaner that easily removes deeply imbedded rust, stains, yellowing, residues and other grime off a variety of boat and marine surfaces. It is a safer alternative to hydrochloric acid and other corrosive cleaners. Xtreme Marine WashDown is NOT a marine pollutant.**

#### **For Use On:**

- Gelcoat, Fiberglass, some Plastics, Rubber, Glass and Stainless Steel
- For vertical / horizontal and interior / exterior surfaces
- For smooth and non-skid surfaces.

#### **Features:**

- Quickly cleans stains, rust and other discolorations from gelcoat, fiberglass, stainless steel and other boat surfaces. (Some surfaces may require re-waxing or re-polishing after use).
- Easily applied by brush or pouring and spreading on surfaces.
- Fume-free formula contains no hydrochloric/muriatic acid
- **The product is NOT a marine pollutant.**

#### **Coverage:**

Approximately 100 – 150 square feet / US Gallon.

**DO NOT ALLOW TO FREEZE. DO NOT DILUTE**

#### **Application Method:**

- Synthetic bristle brush
- Large horizontal areas: Product can be poured on surface and distributed evenly over the surface by squeegee/brush method
- Protect brass (bronze, galvanized zinc), wood, antifouling paint and delicate surfaces from exposure.

#### **Site Conditions & Preparation:**

- Xtreme Marine WashDown should be applied in weather above 5°C
- **Not for use on:** delicate surfaces, wood, Lexan, fabrics, antifouling paint and brass (bronze, galvanized zinc).
- Ensure areas not to be treated are protected, overspray must be wiped off these substrates
- This product will remove wax and some polishes off surfaces. These surfaces will require re-waxing and re-polishing to achieve a uniform finish.

- Performing a test patch will determine substrate suitability, colorfastness and dwell time.

**Dwell Time:**

- **Stubborn and deeply embedded rust and stains should be left to dwell for between 20-30 minutes.**
- Light duty cleaning is achieved with minimal dwell time.
- Do not leave product on surface for extended dwell times especially in hot, direct sun.
- Stubborn stains may require a second application to achieve complete removal.

**Application & Removal:**

- Wash surface to remove loose dirt and debris.
- Surfaces can be dry or damp, but should not have water pooled on the surface as this will dilute the product.
- Apply by brush or pouring directly on the affected areas. Ensure liberal and complete coverage. Protect areas not to be treated from contact with product.
- Leave on for 15 minutes for light duty stains for up to 30 minutes for heavily embedded stains. **Typical dwell time is 20minutes.**
- Do not allow product to dry on the surface. If this occurs, apply more product to reactivate.
- Just prior to removal, agitation with a stiff, synthetic bristle brush will assist in lifting deeply embedded stains.
- Pressure-wash off product and all residues; rinse thoroughly until foam bubbles stop forming.
- If any staining remains, reapply Xtreme Marine WashDown according to the above method
- **ONCE DESIRED RESULTS ARE ACHIEVED, WASH ALL SURFACES WITH SOAPY WATER TO REMOVE REMAINING PRODUCT AND RESIDUES.**
- This product will remove wax from waxed substrates. Surfaces will require re-waxing after use to achieve a uniform surface appearance.
- This product is NOT a marine pollutant.

**Clean-Up:**

- Ensure all unused product is stored in closed containers.
- Xtreme Marine WashDown is biodegradable but always check and comply with local disposal regulations.

**Safety and Personal Protective Equipment:**

- **Use latex gloves. Avoid contact with skin**, if this occurs, wash well with water.
- Use in well ventilated areas – **do not ingest, swallow or inhale**
- In confined spaces always use a painter's mask.
- **Avoid contact with eyes, always wear goggles** – flush well with water if contact occurs

**DISCLAIMER:**

- This product is a heavy duty cleaning product designed for hard to clean applications. Follow all instructions accordingly.
- **Avoid contact with delicate surfaces, wood, Lexan, fabrics, antifouling paint and brass (bronze, galvanized zinc).**